



Goliath Threading Tools Pty Ltd ABN 23 000 534 814  
 336 Victoria Street, Brunswick Victoria Australia 3056  
 PO Box 7, Brunswick Victoria Australia 3056  
 Phone: 03 9387 4755 Fax: 03 9387 9219  
 Int. Phone: +61 3 9387 4755 Int. Fax: +61 3 9387 9219  
 Web: www.goliath.com.au Email: sales@goliath.com.au

## MATERIAL SAFETY DATA SHEET

Date of issue 28/11/2008

### Section 1

**Importer/Supplier:**

**Goliath Threading Tools**  
**336 Victoria Street**  
**Brunswick Vic 3056**  
**Phone: 03 9387 4755**  
**Australian Poisons Ph. 131126**

**Product Name:**

**New Rapid Tap, Paste**

**Chemical Name & Synonyms:**

**Predominantly Chlorinated Paraffin**  
**(49 CFR 172 101)**

### Section 2 (Components)

	TLV	PEL	STEL	C.A.S. No.	Haz*	A.D.G Code	% wt.
Paraffin, Chlorinated	NE	NE	NE	61788-76-9	N/A	N/A	<40
Paraffin wax	2mg/m3	NE	NE	64742-42-3	N/A	N/A	<40
Mineral Oil	5mg/m3	5mg/m3	NE	64742-58-1	N/A	N/A	<10
Metal Cutting Fluid Additive	5mg/m3	10mg/m3	NE	Trade Secret	N/A	N/A	>3
Soybean Oil, epoxidized	NE	NE	NE	8013-07-8	N/A	N/A	>5
Olefin Sulfide	5mg/m3	10mg/m3	NE	Trade Secret	N/A	N/A	<1
Cinnamon Oil Perfume	NE	NE	NE	-- --	N/A	N/A	trace

**Not hazardous according to the criteria of WorkSafe.**

**Haz\*** not listed in National Occupational Health & Safety Commission, List of Designated Hazardous Substances, 1999.  
 Dangerous Goods: Not Classified

### Section 3 (Physical Data)

Boiling Point:	>176.7deg C	Data is based upon testing mixture as a whole.	Freezing Point:	-101.1deg C
Vapor Pressure (mm Hg):	NF	Specific Gravity (H2O=1)@25 C: 1.08	VOC:	Nil
Vapor Density (Air=1):	NF	Percent Volatile by Volume (%): N/A		
Solubility in water:	<0.2%	Evaporation Rate (Water=1): N/A		
Appearance & Odor:	light amber color/solid; slight odor	pH: N/A		Material is Paste

### Section 4 (Fire & Explosion Hazard Data)

Flash Point (method used):	204.4deg C; (COC)	Data is based upon testing mixture as a whole.	Flammable Limits:	LEL	UEL
Extinguishing Media:	Carbon Dioxide, Foam, Dry Chemical, Water, Fog.		Non-Flammable	ND	ND
Special Fire Fighting procedures:	Wear self-contained breathing apparatus with full face piece in a pressure-demand mode; Full-body protective clothing. Treat as oil fire. Cool fire-exposed containers with water spray to prevent rupture.				
Unusual Fire & Explosion Hazards:	Combustion can produce acid gases (hydrogen chloride, hydrogen sulfide)				
Container Handling:	Do <u>not</u> cut or weld empty drums unless thoroughly cleaned. Cool fire-exposed containers with water spray to prevent rupture.				

### Section 5 (Health Hazard Data)

Routes of Entry & Symptoms of Overexposure:	Eyes & Skin: may cause mild irritation. Inhalation: may cause mild upper respiratory irritation. Ingestion: possible nausea.
Emergency & First Aid Procedures:	Eyes: Flush for 15 min's with water. Skin: wash with soap & water. Inhalation: remove to fresh air. Ingestion: Do not induce vomiting: give lots of water to a conscious person. Call Doctor.

### Section 6 (Reactivity Data)

Stability:	Stable	Conditions to avoid:	Elevated temperatures produce decomposition.
Incompatibility (materials to avoid):	Strong oxidizing and reducing agents, strong alkalis, Iron and Zinc catalyze deterioration.		
Hazardous Decomposition Product:	Combustion can produce carbon-dioxide and monoxide, hydrogen chloride, incompletely burned hydrocarbon products, oxides of sulfur & nitrogen, aldehydes, & traces of hydrogen sulfide.		
Hazardous Polymerization:	Will not occur.		
Conditions to avoid:	N/A.		

NE=Not Established

NF=Not Found

N/A=Not Applicable

ND=Not Determined



Goliath Threading Tools Pty Ltd ABN 21 000 534 814  
336 Victoria Street, Brunswick Victoria Australia 3056  
PO Box 7, Brunswick Victoria Australia 3056  
Phone: 03 9387 4755 Fax: 03 9387 9219  
Int. Phone: +61 3 9387 4755 Int. Fax: +61 3 9387 9219  
Web: [www.goliath.com.au](http://www.goliath.com.au) Email: [sales@goliath.com.au](mailto:sales@goliath.com.au)

Page 2

## **New Rapid Tap, Paste**

### **Section 7 (Spill or Leak Procedures)**

Steps to be taken in case material is released or spilled: Clean up promptly by vacuum or absorbent material.  
Prevent discharge to streams or sewage systems; report if required.  
Waste Disposal Method: Transport to EPA-approved treatment, storage and disposal facility.  
Follow local, State disposal regulations.

### **Section 8 (Special Protection Information)**

Respiratory Protection: Normally not needed. For oil-type mist, use NIOSH-listed respirator.  
Ventilation: Local - Adequate to avoid fumes and oil mists. Special: Not required normally.  
Protective Gloves: Rubber / Latex or other impervious gloves to prevent skin exposure.  
Eye Protection: Chemical goggles or full faceshield.  
Other protective equipment: Clean clothes / Apron or chemical suit where splashing may occur.

### **Section 9 (Special precautions)**

Precautions to be taken in handling and storage: Store in a dry place. Vent vapors to open area if stored above 37.8deg C.  
Don't store near food or in zinc or iron containers.  
Other precautions: Chlorinated paraffin will darken at elevated temperatures. Avoid mist and vapor; use with adequate ventilation & Exhaust of work area.

Note: Although no exposure limits are established, observe ACGIH-OSHA TWA for oil mists: 5Mg/meter<sup>3</sup>.  
Use with adequate local ventilation and exhaust devices.

IARC-NTP-OSHA: **Neither the mixture nor any component is listed as a carcinogen or suspected carcinogen.**



# GOLIATH